

Single/Dual Channel High-Voltage Amplifiers



- Precise signal amplification with low distortion
- High Voltage Output up to 400 Vp-p (± 200 V)
- DC-2 MHz small signal bandwidth (-3 dB)
- Full power bandwidth, from DC to 200 kHz (-0.1 dB)
- Single or Dual Channel
- Independent 200:1 voltage monitor outputs for each channel
- Compatible with all TEGAM Arbitrary Waveform and Function Generators
- Compatible with any Signal Generator that can drive a 50 Ω impedance.
- Excellent Choice for MEMS, electrostatic, or piezoelectric applications.

The Models 2340/2350 are designed for applications that require high-voltage amplification beyond the standard voltage limitations of most waveform, function, or pulse generators.

With a maximum output voltage of 400 Vp-p, the Models 2340/2350 come standard with a fixed gain of +50. Gains from 10 to 100 are available by special order.

Each channel is rated for 40 mA continuous current with 0.2 Ω output impedance. Each channel has an independent, buffered, voltage monitor output for applications that require a low-level representation of the output signal. The buffers produce a reduction of 200:1 for 50 Ω inputs and 100:1 for 1 M Ω and above inputs.

The output current is sensed in both directions by the current limit function. This provides maximum protection to the amplifier during

operation. A built-in power supply monitor protects the power amplifiers by tracking the DC power supply. If a high-voltage DC fault occurs, the monitor will disconnect the power supply from the power amplifiers. Cycling the supply power resets the fault. The amplifiers can drive capacitive loads up to 200 pF while maintaining a full power bandwidth exceeding 200 kHz.

For maximum users safety, the outputs are grounded to the instrument chassis to prevent accidental voltage loops. A binding post is provided on the front panel for a direct chassis ground connection.

The Models 2340/2350 are cost-effective solutions for specialized applications where low distortion and precise signal amplification is required. These units are particularly suited for high frequency, electrostatic applications that require high voltage.

Specifications

Electrical Specifications

| | |
|---|---|
| Number of Channels | 1 Channel - Model 2340 or 2 Channel - Model 2350 |
| Input Impedance | 50 Ω Direct Coupled |
| Output Voltage Range | 0 to ± 200 V Direct Coupled (400 V p-p) |
| Maximum Output Current | 40 mA per channel |
| Output Impedance | < 0.2 Ω |
| Voltage Gain | x50 Fixed (Special Order x10-100) |
| Sine Wave Distortion (THD) | Refer to Figure 4 |
| Small Signal Bandwidth | DC to 2 MHz -Typical (-3 dB) - Refer to Figure 1 |
| Full Power | 200 kHz / 400 Vpp Sine - Typical (-0.1 dB) (CL<200 pF) |
| Slew Rate | >250 V/ μ Sec |
| Square Wave Response (10%-90%) | < 0.8 μ Sec for 200 Volt Step |
| Aberrations | < 2 % |
| 50 Ω Voltage Monitor Outputs (One for each Channel) | 50 Ω Input Z (200:1 Ratio) > 1 M Ω Input Z (100:1 Ratio) |

Safety

Conforms with IEC 61010-1, CE Marked

Environmental

| | |
|-----------------------|---|
| Operating Temperature | 0 $^{\circ}$ C to +45 $^{\circ}$ C, (+32 $^{\circ}$ F to +113 $^{\circ}$ F) Ambient |
| Storage Temperature | -20 $^{\circ}$ C to +50 $^{\circ}$ C (-4 $^{\circ}$ F to +122 $^{\circ}$ F) |
| Humidity Range | < 80 % RH Non-Condensing |

General

| | |
|-------------------------|---|
| Input Supply Voltage | 110/220 V 50/60 Hz - Rear Panel Selectable |
| Power Rating | 100 VA; 80 W |
| Dimensions: (H x W x L) | 11.5 x 25.8 x 30.0 cm (4.51 in x 10.14 in x 11.81 in) |
| Weight (approximate) | 4.5 kg (10 lb) |

Included Accessories

| | |
|--|---------------|
| User's Manual | P/N 810044-CD |
| BNC to High-Voltage BNC (SHV-5KV) Cables (3 ft) (1 Cable for P/N 2340, 2 Cables for P/N 2350) | P/N 740949 |

Warranty

1 Year Parts and Labor




Figure 1: Small Signal Frequency Response (Typical)
Amplifier Gain measured with 900 mV peak-to-peak input. Amplifier Frequency Response (-3 dB) at 2 MHz.




Figure 2: Small Signal Frequency Response (Typical)
Amplifier Gain measured with 900 mV peak-to-peak input. Same as Figure 1 but Y-axis is Volts instead of dB.




Figure 3: Maximum Vpp vs. Frequency
Amplifier's maximum peak-to-peak output roll off with frequency. This is due to the amplifier's slew rate of 250 V/ μ Sec.




Figure 4: Distortion (Typical)
Distortion measurements were made operating the amplifier at 75 % of the maximum Vpp output obtained from Figure 3.

