

Photo	Part #	Description
	CBL-3102	3-ft. BNC Cable used for general purpose I/O connections.
	BNC-3285	BNC (F-M-F) BNC Tee Connector used for splitting 50 Ω, BNC-type connections used for trigger, main output, modulation, and sync I/O's.
	1583-3 1583-6 1583-9	3 ft. (1 m) heavy duty, shielded GPIB Buss cable 6 ft. (2 m) heavy duty, shielded GPIB Buss cable 9 ft. (3 m) heavy duty, shielded GPIB Buss cable
NO PHOTO AVAILABLE	810050 810051 810052	Printed user's manual for Model 2720 Printed user's manual for Model 2725 Printed user's manual for Model 2730
NO PHOTO AVAILABLE	2701	Single Unit Rack Mount Kit – fits 2720, 2725, or 2730 function/arbitrary waveform generator.
NO PHOTO AVAILABLE	2702	Dual Unit Rack Mount Kit - allows side-by-side rack mounting of 2720, 2725, or 2730 function/arbitrary waveform generators.
	-	National Instruments LabVIEW™ Driver for Models 2720, 2725, and 2730. Available at no charge.
INCLUDED ACCESSORIES		
	740565-6	6-ft. DB9 to DB9 F/F RS-232C null modem cable for 2720, 2725, and 2730 function/arbitrary waveform generators.
	200024	WaveWorks DDS™ Waveform Creation Software for creating and downloading standard or custom waveforms to the 2700 Series function/arbitrary waveform generators.
	810050-CD 811051-CD 811052-CD	User's manual CD for Model 2720 User's manual CD for Model 2725 User's manual CD for Model 2730
	161006600	Power Cord for 120 VAC Operation. Contact TEGAM for power cords for alternate voltages.